HOW TO GIVE YOUR TRUMPET A BATH

VIDEO TUTORIAL: https://youtu.be/5AyPIfb13hQ

- 1. Fill a large sink, bath tub, or plastic bin with about 4 inches of warm (not hot) water and some dish soap (just one big squirt is enough).
 - a. If the water is too hot, the coating on the trumpet will come off!
- 2. Take out the 3 valves, and lay them somewhere safe where they won't get scratched or dented.
 - a. Do not soak these! There are pieces of felt that will disintegrate if they get wet.
- 3. Take off all of the slides that come off, and lay them in the soapy water.
 - a. If any are stuck, you can leave them on do not try to pull too hard or you may bend or break the trumpet.
- 4. Carefully lay the trumpet, mouthpiece, and all of the slides in the warm soapy water.



- 5. Let soak for 15 minutes (everything but the valves).
- 6. After 15 minutes, use a mouthpiece brush to scrub the inside of your mouthpiece.



- 7. Use a <u>soft</u> brush to scrub the insides of the valve casings (tubes where the valves go).
 - a. Do not scratch these tubes, or else your valves will stick a lot! If you don't have a soft brush, skip this step!



8. Use a trumpet snake (a brush on a long wire) to scrub the insides of the slides, as well as all of the tubes on the trumpet (but **not** where your valves go – too scratchy!)



- 9. Take each valve one at a time (remember not to soak them!) and rinse the bottom half under warm water. Use your fingers to rub dish soap on them to clean them, without scratching them.
 - a. Try not to get the top halves too wet (where you put your fingers), or else the felt pieces will disintegrate!
- 10. Rinse everything thoroughly to get rid of any soap.
- 11.Lay all of the parts out on a soft towel for several hours so they can drain and drip-dry.
- 12.Once everything is dry, you can re-assemble your trumpet, **oil your valves**, put a little bit of slide grease on each of your tuning slides so they don't get stuck, and put it back in the case!